

OUTDOOR – MARINE, LILIAN, LILIAN STRIPES, LINEN, CAPRI, RIMINI

SESTAVA COMPOSITION SIROVINSKI SASTAV ZUSAMMENSETZUNG COMPOSIZIONE		100% POLIOLEFIN 100% POLYOLEFIN 100% POLIOLEFINSKO VLAKNO 100% POLYOLEFIN 100% POLYOLEFIN	
ŠIRINA WIDTH ŠIRINA BREITE ALTEZZA	160 cm	TEŽA WEIGHT TEŽINA GEWICHT PESO	190 gr/m2

TEST	STANDARD	REZULTAT/RESULTS/REZULTAT/ERGEBNIS / RISULTATO	
		OSNOVA/WARP/ OSNOVA/KETTE / ORDITO	VOTEK/WEFT/ POTKA/SCHUSS / TRAMA
RAZTEZNA TRDNOST TENSILE STRENGTH ČVRSTOČA NA RASTEZANJE ZUGFESTIGKEIT RESISTENZA ALLA TRAZIONE	EN ISO 13934-1	1647 N	740 N
RAZTRŽNA TRDNOST TEAR STRENGTH ČVRSTOČA NA KIDANJE WEITERREISSFESTIGKEIT RESISTENZA ALLA LACERAZIONE	EN ISO 13937-3	73,9 N	43,18 N
DRSNOST NITI RESISTANCE TO SEAM SLIPPAGE OTPORNOST NA POMJERANJE /POMERANJE ŠAVA NAHTSCHIEBEWIDERSTAND RESISTENZA ALLO SCORRIMENTO DELLA CUCITURA	prEN ISO 13936-2 PRI/AT/KOD/BEI 180 N	3,0 mm	3,0 mm
OBSTOJNOST TKANINE NA DRGNJENJE ABRASION RESISTANCE POSTOJANOST TKANINE NA TRLJANJE SCHEUERBESTAENDIGKEIT RESISTENZA ALL'ABRASIONE	DIN EN ISO 12947-1 DIN EN ISO 12947-2	20.000 OBRATOV/REVS./OBRTAJA /TOUREN / GIRI	
PILING PILLING RESISTANCE PILING PILLBILDUNG RESISTENZA AL PILLING	EN ISO 12945-2 2.000 OBRATOV/REVS./OBRTAJA /SCHEUERTOUREN / GIRI	5	
OBSTOJNOST BARVE NA SVETLOBO COLOUR FASTNESS TO LIGHT POSTOJANOST BOJE NA SVJETLO/SVETLOST LICHTECHTHEIT SOLIDITA DEL COLORE ALLA LUCE	EN ISO 105-B02	7-8	
OBSTOJNOST BARVE NA DRGNJENJE COLOUR FASTNESS TO RUBBING POSTOJANOST BOJE NA TRLJANJE REIBECHTHEIT SOLIDITA DEL COLORE ALL'ABRASIONE	EN ISO 105-X12	SUHO/DRY/SUHO/ SUVO/TROCKEN / SECCO	MOKRO/WET/ MOKRO/NASS / UMIDO
<p>VARUJE KOŽO. BLOKIRA VEČ KOT 97% UV ŽARKOV. <u>CERTIFIKAT UV STANDARD 801</u>. STOPNJA ZAŠČITE UPF 80. PROTECTS YOUR SKIN, BLOCKING MORE THEN 97% UV RAYS. FABRIC WITH <u>UV STANDARD 801 CERTIFICATE</u>. LEVEL OF PROTECTION UPF 80 ŠTITI KOŽU. BLOKIRA VIŠE OD 97% UV ZRAKA. <u>CERTIFIKAT UV STANDARD 801</u>. STUPANJ/STEPEN ZAŠTITE UPF 80 SCHONT DAS HAUT. BLOCKIERT MEHR ALS 97% VON UV STRAHLUNG. <u>ZERTIFIKAT UV STANDARD 801</u>. UV-SCHUTZFAKTOR 80. PROTEGGE LA PELLE BLOCCANDO OLTRE IL 97% DEI RAGGI UV, TESSUTO CON <u>CERTIFICATO UV STANDARD 801</u>, LIVELLO DI PROTEZIONE UPF 80.</p>			

MERCIS d.o.o., Puchova ulica 3, 1235 Radomlje, Slovenija ID: SI13107631

Tel. +386 1 4700700 Fax +386 1 4700720 e-mail:mercis@mercis.si

MERCIS

fabrics and leathers

OEKO TEX CERTIFIKAT: CLASS 1 (ARTIKEL PRIMEREN ZA OTROKE). NE POVZROČA ALERGIJ
OEKO TEX CERTIFICATE: CLASS 1 (ARTICLES FOR BABIES). NON ALLERGIC
OEKO TEX CERTIFIKAT: CLASS 1 (ARTIKAL PRIMJERAN/PRIMERAN ZA DJECU/DECU). NE UZROKUJE ALERGIJE
OEKO TEX ZERTIFIKAT: KLASSE 1 (ARTIKEL FÜR KLEINKINDER GEEIGNET). NICHT ALLERGISCH.
CERTIFICATO OEKO TEX: CLASSE 1 (ARTICOLI PER BAMBINI, NON ALLERGENICO)

ZAŠČITA PROTI PREPEREVANJU / ZAŠČITA PROTI TROHNENJU / VODOODBOJNA APRETURA / 100% RECIKLAŽEN
PROTECTION AGAINST SUNLIGHT DEGRADATION / ROT PROOF / WATER REPELLENT FINISH/100% RECYCIABLE
ZAŠTITA PROTIV RASPADANJA / ZAŠTITA PROTIV TRULJENJA / VODOODBOJNA APRETURA/100% RECIKLAŽAN
VERWITTERUNGSSCHUTZ / VERROTTUNGSSCHUTZ/WASSERABPRALLUNGSAPPRETUR / 100% WIEDERVERWERTUNG
PROTEZIONE CONTRO LA DEGRADAZIONE SOLARE / IMPUTRESCIBILE / FINISSAGGIO IDROREPELENTE / 100% RICILABILE

MED BARVNIMI PARTIJAMI SO MOŽNA ODPSTAPANJA V BARVI
COLOUR DIFERENCES BETWEEN DYING LOTS ARE POSSIBLE
MOGUČA SU ODPSTAPANJA U BOJI KOD PROIZVODNJE
FARBABWEICHUNGEN SIND MOEGLICH
TRA I VARI LOTTI POSSONO VERIFICARSI DELLE VARIAZIONI NEL COLORE.



MERCIS d.o.o., Puchova ulica 3, 1235 Radomlje, Slovenija ID: SI13107631
Tel. +386 1 4700700 Fax +386 1 4700720 e-mail:mercis@mercis.si

BANK: ABANKA VIPA D.D. LJUBLJANA

IBAN SI56051008000023369

SWIFT CODE: ABANSI2X