

OUTDOOR - CAPRI, CORAL, LILIAN, LILIAN STRIPES, LINEN, MARINE, RIMINI, SUN

SESTAVA COMPOSITION SIROVINSKI SASTAV ZUSAMMENSETZUNG COMPOSIZIONE		100% POLIOLEFIN 100% POLYOLEFIN 100% POLIOLEFIN 100% POLYOLEFIN 100% POLYOLEFIN	
ŠIRINA WIDTH ŠIRINA BREITE ALTEZZA	160 cm ±2%	TEŽA WEIGHT TEŽINA GEWICHT PESO	190 g/m ² ±5%
TEST	STANDARD	REZULTAT/RESULTS/REZULTAT /ERGBNIS RISULTATI	
		OSNOVA/WARP/ OSNOVA/KETTE/ORDITO	VOTEK/WEFT/ POTKA/SCHUSS/TRAMA
RAZTEZNA TRDNOST TENSILE STRENGTH ČVRSTOČA NA RASTEZANJE ZUGFESTIGKEIT RESISTENZA ALLA TRAZIONE	EN ISO 13934-1	1647 N	740 N
DRSNOST NITI RESISTANCE TO SEAM SLIPPAGE OTPORNOST NA POMJERANJE / POMERANJE ŠAVA NAHTSCHIEBEWIDERSTAND RESISTENZA ALLO SCORRIMENTO DELLA CUCITURA	EN ISO 13936-2 PRI/AT/KOD/BEI /A180 N	3 mm	3 mm
RAZTRŽNA TRDNOST TEAR STRENGTH ČVRSTOČA NA KIDANJE WEITERREISSFESTIGKEIT RESISTENZA ALLA LACERAZIONE	EN ISO 13937-3	74 N	44 N
PILING PILLING RESISTANCE PILING PILLBILDUNG RESISTENZA AL PILLING	EN ISO 12945-2 2.000 OBRATOV / REVS. / OBRTAJA / SCHEUERTOUREN / GIRI	5	
OBSTOJNOST TKANINE NA DRGNJENJE ABRASION RESISTANCE POSTOJANOST TKANINE NA TRLJANJE SCHEUERBESTAENDIGKEIT RESISTENZA TESSUTO ALL'ABRASIONE	EN ISO 12947-2	20.000 OBRATOV/REVS./ OBRTAJA /TOUREN/GIRI	
OBSTOJNOST BARVE NA SVETLOBO COLOUR FASTNESS TO LIGHT POSTOJANOST BOJE NA SVJETLO/SVETLOST LICHTECHTHEIT RESISTENZA ALLA LUCE	EN ISO 105-B02	7-8	
OBSTOJNOST BARVE NA DRGNJENJE COLOUR FASTNESS TO RUBBING POSTOJANOST BOJE NA TRLJANJE REIBECHTHEIT SOLIDITA DEL COLORE ALL'ABRASIONE	EN ISO 105-X12	SUHO/DRY/SUHO/ SUVO/TROCKEN / SECCO	MOKRO/WET/ MOKRO/NASS / UMIDO
		4-5	4-5
UV ZAŠČITA UV FACTOR PROTECTION UV ZAŠTITA UV SCHUTZ FATTORE UV	UV STANDARD 801	UPF 80 - BLOKIRA VEČ KOT 97% UV ŽARKOV. VARUJE KOŽO. UPF 80 - BLOCKS MORE THAN 97% UV RAYS. PROTECTS YOUR SKIN. UPF 80 - BLOKIRA VIŠE OD 97% UV ZRAKA. ŠTITI KOŽU. UPF 80 - BLOCKIERT MEHR ALS 97% VON UV STRAHLUNG. SCHONT DIE HAUT. UPF 80 - BLOCCANDO OLTRE IL 97% DEI RAGGI UV. PROTEGGE LA PELLE.	
ZAŠČITA PROTI PREPEREVANJU / ZAŠČITA PROTI TROHNENJU / VODOODBOJNA APRETURA / 100% RECIKLAŽEN PROTECTION AGAINST SUNLIGHT DEGRADATION / ROT PROOF / WATER REPELLENT FINISH/100% RECYCLABLE ZAŠTITA PROTIV RASPADANJA / ZAŠTITA PROTIV TRULJENJA / VODOODBOJNA APRETURA/100% RECIKLAŽAN VERWITTERUNGSSCHUTZ / VERROTTUNGSSCHUTZ/WASSERABPRALLUNGSAPPRETUR / 100% WIEDERVERWERTBAR PROTEZIONE CONTRO LA DEGRADAZIONE SOLARE / IMPUTRESCIBILE / FINISSAGGIO IDROREPELENTE / 100% RICILABILE			
TEST NEGORLJIVOSTI FIRE RETARDANT TEST NEGORIVOSTI BRENNVERHALTEN IGNIFUGO	BS 5852 source 0 Without Soaking	PRESTAL TEST PASSED PROŠAO TEST UEBERSTANDEN SUPERATO	

MED BARVNIMI PARTIJAMI SO MOŽNA ODPSTAPANJA V BARVI // COLOUR DIFERENCES BETWEEN DYING LOTS ARE POSSIBLE //
MOGUĆA SU ODPSTAPANJA U BOJI KOD PROIZVODNJE // FARBNUANCEN SIND MOEGLICH //
DIFFERENZE DI COLORE TRA I LOTTI DI TINTURA SONO POSSIBILI

