

OUTDOOR SORRENTO CHECK

SESTAVA COMPOSITION SIROVINSKI SASTAV ZUSAMMENSETZUNG COMPOSIZIONE		100% AKRIL, DRALON® 100% ACRYLIC, DRALON® 100% AKRILNO VLAKNO, DRALON® 100% ACRYL, DRALON® 100% ACRILICA, DRALON®	
ŠIRINA WIDTH ŠIRINA BREITE ALTEZZA	160 cm ±2%	TEŽA WEIGHT TEŽINA GEWICHT PESO	185 g/m ² ±5%

TEST	STANDARD	
OBSTOJNOST TKANINE NA DRGNJENJE ABRASION RESISTANCE POSTOJANOST TKANINE NA TRLJANJE SCHEUERBESTAENDIGKEIT RESISTENZA TESSUTO ALL'ABRASIONE	DIN EN ISO 12947	OBRATOV/REVS./ OBRTAJA /TOUREN/GIRI 25.000
PILING PILLING RESISTANCE PILING PILLBILDUNG RESISTENZA PILLING	EN ISO 12945-2: 2.001	4-5
OBSTOJNOST BARVE NA SVETLOBO COLOUR FASTNESS TO LIGHT POSTOJANOST BOJE NA SVJETLO/SVETLOST LICHTECHTHEIT RESISTENZA ALLA LUCE	EN ISO 105-B02	5-8 ODVISNO OD BARVE/PENDING ON COLOUR/ODVISNO OD BOJE/JE NACH FARBE/DIPENDE DAL COLORE
OBSTOJNOST BARVE NA DRGNJENJE COLOUR FASTNESS TO RUBBING POSTOJANOST BOJE NA TRLJANJE REIBECHTHEIT RESISTENZA COLORI ALL' ABRASIONE	EN ISO 105-X12	5 ODVISNO OD BARVE/PENDING ON COLOUR/ODVISNO OD BOJE/JE NACH FARBE/DIPENDE DAL COLORE
OBSTOJNOST BARVE NA PRANJE COLOUR FASTNESS TO WASHING POSTOJANOST BOJE NA PRANJE FARBECHTHEIT GEGEN WASCHEN RESISTENZA COLORI AL LAVAGGIO	EN ISO 105-C06:2010	5
OBSTOJNOST BARVE NA BELJENJE COLOUR FASTNESS TO BLEACHING POSTOJANOST BOJE NA BELJENJE FARBECHTHEIT GEGEN BLEICHE RESISTENZA COLORI ALL'IMBIANCATURA	UNE-EN 20105- N01:1996	5
OBSTOJNOST BARVE NA MORSKO VODO COLOUR FASTNESS TO SEA WATER POSTOJANOST BOJE NA MORSKU VODU FARBECHTHEIT GEGEN MEERWASSER RESISTENZA COLORI ALL'ACQUA MARINA	EN ISO 105-E02	5
OBSTOJNOST BARVE NA KLOR COLOUR FASTNESS TO CHLORINATED WATER POSTOJANOST BOJE NA KLOR FARBECHTHEIT GEGEN GECHLORTES WASSER RESISTENZA COLORI AL CLORO	EN ISO 105-E03	4-5
PREPUŠCANJE VODE WATER PENETRATION PROPUŠTANJE VODE WASSERDURCHLÄSSIGKEIT PENETRAZIONE DELL'ACQUA	BS EN 20811, ISO 811, 1992-1981	500 mm H ₂ O
OBSTOJNOST NA VODO- TEFLON® WATER REPELLENCY - TEFLON® POSTOJANOST NA VODU -TEFLON® WASSERBESTÄNDIGKEIT IDROPELLENZA	ISO 4920	4-5
OBSTOJNOST NA OLJE – TEFLON® OIL REPELLENCY – TEFLON® POSJOJANOST NA ULJE – TEFLON® ÖLBESTÄNDIGKEIT RESISTENZA AGLI OLI	ISO 14419 40°C	6
UV ZAŠČITA UV FACTOR PROTECTION UV ZAŠTITA UV SCHUTZ FATTORE UV	AS/NZS 4399/1996	UV40 STANDARD 801
OEOTEX STANDARD 100		DA/YES/DA/JA/SI

MERCIS

fabrics and leathers

MED BARVNIMI PARTIJAMI SO MOŽNA ODSSTOPANJA V BARVI
COLOUR DIFERENCES BETWEEN DYING LOTS ARE POSSIBLE
MOGUĆA SU ODSSTOPANJA U BOJI KOD PROIZVODNJE
FARBNUANCEN SIND MOEGLICH
DIFFERENZE DI COLORE TRA I LOTTI DI TINTURA SONO POSSIBILI

